

WASSERDRUCKMINDERER LIEFERPROGRAMM

PN (bar)	Anschluß-flansch	DN (mm)	Baunummer	R	L (mm)	H (mm)	max. Gewicht (Kg)
		100	T 413	1,3	350	333	68
		100	T 415	1,5	350	333	68
		100	T 420	2,0	350	333	68
		100	T 425	2,5	350	333	68
		100	T 430	3,0	350	333	68
		100	T 440	4,0	350	333	68
		100	T 450	5,0	350	333	68
		150	T 613	1,3	480	470	195
		150	T 615	1,5	480	470	195
		150	T 620	2,0	480	470	195
		150	T 625	2,5	480	470	195
		150	T 630	3,0	480	470	195
		150	T 640	4,0	480	470	195
		150	T 650	5,0	480	470	195
		200	T 813	1,3	600	510	280
		200	T 815	1,5	600	510	280
		200	T 820	2,0	600	510	280
		200	T 825	2,5	600	510	280
		200	T 830	3,0	600	510	280
		200	T 840	4,0	600	510	280
		200	T 850	5,0	600	510	280
		250	T 1013	1,3	660	550	330
		250	T 1015	1,5	660	550	330
		250	T 1020	2,0	660	550	330
		250	T 1025	2,5	660	550	330
		250	T 1030	3,0	660	550	330
		250	T 1040	4,0	660	550	330
		250	T 1050	5,0	660	550	330

Für alle Ausführungen:

PN 16	DIN 2633
PN 25	DIN 2634
PN 40	DIN 2635
PN 64	DIN 2636
PN 100	DIN 2637

Alle Ausführungen sind auf Wunsch ohne Anschlußbohrungen lieferbar.